

Model: LPS16-35AP5				
Dimenzion (W/H/L)	157mm*85mm*150mm			
Connectors	24 pin with detachable 4pin section: 1PCE	1		
	4+4 pin 12 V: 1PCE	1		
	8 pin 12 V:Option	option		
	PCI Express: 1PCE 6P	1		
	SATA: 4PCS	4		
	Molex: (B4P) 2PCS	2		
	FDD: 1PCE	1		
	FAN ONLY:1PCE	1		
	Fan RPM Monitor: OK	OK		
Colour	Black			
Fan colour	orange			
Fan diameter	12CM			
power	350W			
ATX (1.3/2.0/2.1/2.2)	2.31			
Input	Power efficiency:	80%		
	Input Voltage:	110*240V only		
	Input frequency Range:	47~63Hz		
	Inrush Current:	80A @ 230Vrms(at 25℃ ambient cold start)		
	Input Current:	4-8A		
Environmental	Operating Altitude:	10,000FT max		
	Storage and shipping conditions:	50,000FT max		
	Dielectric strength:	N/A		
	MTBF:	50,000 hours of continuous operation at 25℃		
	Safety Approvals:	CE TÜV		
	Hold-up time:	16ms		
Safety Protection	Over current protection (OCP):	ok		
	Over Voltage protection (OVP):	OK		
	Short Circuit Protection (SCP):	OK		
	Under Voltage Protection (UVP):	Ok		
	Over Temperature Protection (OTP):	N/A		
	Over Power Protection (OPP):	OK		
PFC (active or passive)	Active Passive			
	+ 3.3 V	+ 5 V	+ 12 V1/+12V2	- 12 V
Min. load	0.3A	0.5A	1A/1A	0.1A
Max. load	18A	20A	12A/13A	0.5A
Load Reg.	+3.14~+3.47(±5%)	+4.75~+5.25(±5%)	+11.4~+12.7(±5%)	-10.8~-13.2(±10%)
Ripple & Noise	100mV.p-p	100mV.p-p	120mV.p-p	200mV.p-p

